



LAKSHMI ELECTRICAL DRIVES PRIVATE LIMITED.,

Coimbatore - 641 004.

TECHNICAL DATA SHEET - 0.25 kW 4 POLE INDUCTION MOTOR

| | | |
|----|-------------------------------------|-----------------------------|
| 1 | Customer : | |
| 2 | Product no : | LE07143006 |
| 3 | Output power (kW) | 0.25 |
| 4 | Output power (HP) | 0.35 |
| 5 | Phase | 3 |
| 6 | Polarity | 4 |
| 7 | Frame | 71 |
| 8 | Voltage (V) | 415±10% |
| 9 | Frequency & it's variation (Hz) | 50±5% |
| 10 | Connection | STAR |
| 11 | Insulation class | F |
| 12 | Ambient temp (Deg. C) | 50 |
| 13 | Duty | S1 |
| 14 | Mounting | B3 |
| 15 | Appllicable code | IS12615/IEC 60034-1 |
| 16 | Type reference | Sq.Cage Induction motor |
| 17 | Full Load Current (Amps) | 8.73/5.02 |
| 18 | Full Load Torque -(Nm) | 1.76 |
| 19 | Full Load Speed (rpm) | 1450 |
| 20 | Starting Current as % of FLC | 500 |
| 21 | Starting Torque as % of FLT | 180 |
| 22 | Brake down or Pull out Torque % FLT | 240 |
| 23 | %Efficiency at 100% | 68.5 (IE2) |
| 24 | at 75% | 66.2 |
| 25 | at 50% | 60.5 |
| 26 | Power factor at 100% | 0.65 |
| 27 | at 75% | 0.62 |
| 28 | at 50% | 0.59 |
| 29 | Temperature Rise | B CLASS LIMIT |
| 30 | Service Factor | 1 |
| 31 | Moment of Inertia | 0.00232 |
| 32 | Direction of Rotation | Bidirectional |
| 33 | Coupling/Pulley | Direct/Flexible |
| 34 | Method of Cooling | IC411 |
| 35 | Enclosure | TEFC |
| 36 | Protection | IP55 |
| 37 | Bearing type | Deep Groove Ball Bearing |
| 38 | Bearing no. DE/NDE | 6203 2RS / 6203 2RS |
| 39 | Paint/Coating | RAL 7032 |
| 40 | Material of Construction | Aluminium |
| 41 | Shaft Material | EN8 |
| 42 | Relative Humidity | <90 |
| 43 | Terminal box position | TOP |
| 44 | No of terminals | 3 |
| 45 | Working Altitude level. | 1000 MT |
| 46 | Additonal Requirement | As per customer requirement |

Efficiency Values are without seals.

Performance Data subject to tolerance as per IS:12615:2018