



LAKSHMI ELECTRICAL DRIVES PRIVATE LIMITED.,

Coimbatore - 641 004.

TECHNICAL DATA SHEET - 0.37 kW 2 POLE INDUCTION MOTOR

1	Customer :	-
2	Product no :	LE07123001
3	Output power (kW)	0.37
4	Output power (HP)	0.5
5	Phase	3
6	Polarity	2
7	Frame	71F
8	Voltage (V)	415±10%
9	Frequency & its variation (Hz)	50±5%
10	Connection	STAR
11	Insulation class	F
12	Ambient temp (Deg. C)	50
13	Duty	S1
14	Mounting	B3
15	Aplicable code	IS12615/IEC 60034-1
16	Type reference	Sq.Cage Induction motor
17	Full Load Current (Amps)	1.2
18	Full Load Torque -(Nm)	1.28
19	Full Load Speed (rpm)	2750
20	Starting Current as % of FLC	500
21	Starting Torque as % of FLT	180
22	Brake down or Pull out Torque % FLT	240
23	%Efficiency at 100%	69.5 (IE2)
24	at 75%	69.5
25	at 50%	65
26	Power factor at 100%	0.78
27	at 75%	0.73
28	at 50%	0.67
29	Temperature Rise	B CLASS LIMIT
30	Service Factor	1.2
31	Moment of Inertia	0.00184
32	Direction of Rotation	Bidirectional
33	Coupling/Pulley	Direct/Flexible
34	Method of Cooling	IC411
35	Enclosure	TEFC
36	Protection	IP55
37	Bearing type	Deep Groove Ball Bearing
38	Bearing no. DE/NDE	6203 2RS / 6203 2RS
39	Paint/Coating	RAL 7032
40	Material of Construction	Aluminium
41	Shaft Material	EN8
42	Relative Humidity	<90
43	Terminal box position	TOP
44	No of terminals	3
45	Working Altitude level.	1000 MT
46	Additional Requirement	As per customer request

Efficiency Values are without seals.

Performance Data subject to tolerance as per IS:12615:2018