

LAKSHMI ELECTRICAL DRIVES PRIVATE LIMITED.,

Coimbatore - 641 004.

TECHNICAL DATA SHEET - 0.55 kW 2 POLE INDUCTION MOTOR

1	Customer :	•
2	Product no :	LE07125002
3	Output power (kW)	0.55
4	Output power (HP)	0.75
5	Phase	3
6	Polarity	2
7	Frame	71F
8	Voltage (V)	415±10%
9	Frequency & it's variation (Hz)	50±5%
10	Connection	STAR
11	Insulation class	F
12	Ambient temp (Deg. C)	50
13	Duty	S1
14	Mounting	B5
15	Apllicable code	IS12615/IEC 60034-1
16	Type reference	Sq.Cage Induction motor
17	Full Load Current (Amps)	1.6
18	Full Load Torque -(Nm)	1.9
19	Full Load Speed (rpm)	2770
20	Starting Current as % of FLC	500
21	Starting Torque as % of FLT	190
22	Brake down or Pull out Torque % FLT	250
23	%Efficiency at 100%	74.1 (IE2)
24	at 75%	74
25	at 50%	70
26	Power factor at 100%	0.79
27	at 75%	0.74
28	at 50%	0.68
29	Temperature Rise	B CLASS LIMIT
30	Service Factor	1.2
31	Moment of Inertia	0.00232
32	Direction of Rotation	Bidirectional
33	Coupling/Pulley	Direct/Flexible
34	Method of Cooling	IC411
35	Enclosure	TEFC
36 37	Protection	IP55
	Bearing type	Deep Groove Ball Bearing
38 39	Bearing no. DE/NDE	6203 2RS / 6203 2RS RAL 7032
39 40	Paint/Coating	Aluminium
40 41	Material of Construction Shaft Material	EN8
41 42		<90
42 43	Relative Humidity Terminal box position	TOP
43 44	No of terminals	3
44 45	Working Altitude level.	1000 MT
45 46	Additonal Requirement	As per customer request
+∪	Additional Dequirement	Typ her charottier reducar
	Efficiency Values are without seals.	