

LAKSHMI ELECTRICAL DRIVES PRIVATE LIMITED.,

Coimbatore - 641 004.

TECHNICAL DATA SHEET - 11 kW 2 POLE INDUCTION MOTOR

<u>1</u> 2	Product no :	LE16025004
<u>2 </u>		11
	Output power (kW)	
4	Output power (HP)	15
5	Phase	3
<u>6</u>	Polarity	2
7	Frame	160M
8	Voltage (V)	415±10%
9	Frequency & it's variation (Hz)	50±5%
0 1	Connection	DELTA
	Insulation class	F
2	Ambient temp (Deg. C)	50
3	Duty	S1
4	Mounting	B5
15	Apllicable code	IS12615/IEC 60034-1
6 7	Type reference	Sq.Cage Induction motor
	Full Load Current (Amps)	19
8 9	Full Load Torque -(Nm) Full Load Speed (rpm)	35.8
	Starting Current as % of FLC	2940
20 21	Starting Torque as % of FLT	700
	Brake down or Pull out Torque % FLT	200
22 23	%Efficiency at 100%	280
	at 75%	89.4 (IE2)
24 25	at 50%	89.4 87
		-
26 27	Power factor at 100% at 75%	0.88
28	at 75%	0.76
<u>29</u>	Temperature Rise	B CLASS LIMIT
30	Service Factor	1.2
31	Moment of Inertia	0.226
32	Direction of Rotation	Bidirectional
33	Coupling/Pulley	Direct/Flexible
34	Method of Cooling	IC411
35	Enclosure	TEFC
36	Protection	IP55
37	Bearing type	Deep Groove Ball Bearing
38	Bearing no. DE/NDE	6309ZZ C3 / 6309ZZ C3
39	Paint/Coating	RAL 7032
10	Material of Construction	CI FG200
11	Shaft Material	EN8
2	Relative Humidity	<90
13	Terminal box position	TOP
4	No of terminals	6
15	Working Altitude level.	1000 MT
6	Additonal Requirement	As per customer request
_		The particular request