



LAKSHMI ELECTRICAL DRIVES PRIVATE LIMITED.,

Coimbatore - 641 004.

TECHNICAL DATA SHEET - 15 kW 2 POLE INDUCTION MOTOR

| | | |
|--|-------------------------------------|--------------------------|
| 1 | Customer : | - |
| 2 | Product no : | LE16023003 |
| 3 | Output power (kW) | 15 |
| 4 | Output power (HP) | 20 |
| 5 | Phase | 3 |
| 6 | Polarity | 2 |
| 7 | Frame | 160M |
| 8 | Voltage (V) | 415±10% |
| 9 | Frequency & it's variation (Hz) | 50±5% |
| 10 | Connection | DELTA |
| 11 | Insulation class | F |
| 12 | Ambient temp (Deg. C) | 50 |
| 13 | Duty | S1 |
| 14 | Mounting | B3 |
| 15 | Appllicable code | IS12615/IEC 60034-1 |
| 16 | Type reference | Sq.Cage Induction motor |
| 17 | Full Load Current (Amps) | 26 |
| 18 | Full Load Torque -(Nm) | 48.9 |
| 19 | Full Load Speed (rpm) | 2940 |
| 20 | Starting Current as % of FLC | 700 |
| 21 | Starting Torque as % of FLT | 200 |
| 22 | Brake down or Pull out Torque % FLT | 280 |
| 23 | %Efficiency at 100% | 90.3 (IE2) |
| 24 | at 75% | 90 |
| 25 | at 50% | 88 |
| 26 | Power factor at 100% | 0.88 |
| 27 | at 75% | 0.88 |
| 28 | at 50% | 0.82 |
| 29 | Temperature Rise | B CLASS LIMIT |
| 30 | Service Factor | 1.2 |
| 31 | Moment of Inertia | 0.256 |
| 32 | Direction of Rotation | Bidirectional |
| 33 | Coupling/Pulley | Direct/Flexible |
| 34 | Method of Cooling | IC411 |
| 35 | Enclosure | TEFC |
| 36 | Protection | IP55 |
| 37 | Bearing type | Deep Groove Ball Bearing |
| 38 | Bearing no. DE/NDE | 6309ZZ C3 / 6309ZZ C3 |
| 39 | Paint/Coating | RAL 7032 |
| 40 | Material of Construction | CI FG200 |
| 41 | Shaft Material | EN8 |
| 42 | Relative Humidity | <90 |
| 43 | Terminal box position | TOP |
| 44 | No of terminals | 6 |
| 45 | Working Altitude level. | 1000 MT |
| 46 | Additional Requirement | As per customer request |
| Efficiency Values are without seals. | | |
| Performance Data subject to tolerance as per IS:12615:2018 | | |