

LAKSHMI ELECTRICAL DRIVES PRIVATE LIMITED.,

Coimbatore - 641 004.

TECHNICAL DATA SHEET - 5.5 kW 2 POLE INDUCTION MOTOR

| 1 | Customer: | |
|-----------------|---|--------------------------|
| 2 | Product no : | LE13223001 |
| 3 | Output power (kW) | 5.5 |
| 4 | Output power (HP) | 7.5 |
| 5 | Phase | 3 |
| 6 | Polarity | 2 |
| 7 | Frame | 132S |
| 8 | Voltage (V) | 415±10% |
| 9 | Frequency & it's variation (Hz) | 50±5% |
| 10 | Connection | DELTA |
| 11 | Insulation class | F |
| 12 | Ambient temp (Deg. C) | 50 |
| 13 | Duty | S1 |
| 14 | Mounting | B3 |
| 15 | Apllicable code | IS12615/IEC 60034-1 |
| 16 17 | Type reference | Sq.Cage Induction motor |
| | Full Load Current (Amps) Full Load Torque -(Nm) | 11 |
| 18 19 | Full Load Speed (rpm) | 18.11 |
| | Starting Current as % of FLC | 2900 |
| 20 21 | Starting Torque as % of FLT | 650 |
| 22 | Brake down or Pull out Torque % FLT | 200 260 |
| <u>22</u> 23 | %Efficiency at 100% | 87.0 (IE2) |
| 24 24 | at 75% | 87.0 (IEZ) |
| 25 | at 50% | 86 |
| 26 | Power factor at 100% | 0.89 |
| <u>27</u> 27 | at 75% | 0.86 |
| 28 | at 50% | 0.8 |
| 2 9 | Temperature Rise | B CLASS LIMIT |
| 30 | Service Factor | 1.2 |
| 31 | Moment of Inertia | 0.056 |
| 32 | Direction of Rotation | Bidirectional |
| 33 | Coupling/Pulley | Direct/Flexible |
| 34 | Method of Cooling | IC411 |
| 35 | Enclosure | TEFC |
| 36 | Protection | IP55 |
| 37 | Bearing type | Deep Groove Ball Bearing |
| 38 | Bearing no. DE/NDE | 6308ZZ C3 / 6307ZZ C3 |
| 39 | Paint/Coating | RAL 7032 |
| 40 | Material of Construction | CI FG200 |
| 41 | Shaft Material | EN8 |
| 42 | Relative Humidity | <90 |
| 43 | Terminal box position | TOP |
| 44 | No of terminals | 6 |
| 45 | Working Altitude level. | 1000 MT |
| 46 | Additonal Requirement | As per customer request |
| | Efficiency Values are without seals. | |