



| NAME PLATE DETAILS (IS 12615 : 2018) | |
|--------------------------------------|-----------|
| MARKING | CE |
| Frame | LE 160 M |
| Duty | S1 |
| Class of insulation | F |
| Frequency, Hz | 50 ±5% |
| Pole | 4 |
| Connectoin | Delta |
| Output in KW | 11 |
| Voltage in volts | 415 ±10% |
| F.L.Current in Amps | 22 |
| Speed in RPM | 1440 |
| % Efficiency | 89.8(IE2) |
| Protection | IP-55 |
| Power Factor | 0.76 |
| BRG DE | 6309 ZZC3 |
| BRG NDE | 6309 ZZC3 |

SAP CODE - 70-0287

| | | | | | | | | | |
|-------------------------------|--------------------|-------------|------|------|-----------|---------------|----------------|--|------------|
| ALL DIMENSIONS ARE IN mm | | | | | PREPARED | H.H | 02-12-2023 | LAKSHMI ELECTRICAL DRIVES LIMITED COIMBATORE - 641 004 | |
| LINEAR DIMENSIONS (MACHINING) | GENERAL TOLERANCES | | | | | CHECKED | V.B | | 02-12-2023 |
| | ABOVE | 0 | 30 | 100 | 300 | APPROVED | R.R | | 02-12-2023 |
| | UPTO | 30 | 100 | 300 | 1000 | SCALE | NTS | | |
| | TOL | ±0.2 | ±0.3 | ±0.5 | ±0.8 | QUANTITY | 1 No | | |
| ANGLES | ± 1/2' | | | | | MATERIAL | | | |
| DCR. NO | ZONE | ALTERATIONS | | | SIGN/DATE | WEIGHT IN kg. | ROUGH FINISHED | RAW MATERIAL CODE | |
| | | | | | | | | MODEL LE 160 M DRG.No. LE16043001 REV. NO 00 | |