



NAME PLATE DETAILS (IS 12615 : 2018)	
MARKING	CE
Frame	LE 160 M
Duty	S1
Class of insulation	F
Frequency, Hz	50 ±5%
Pole	2
Connectoin	Delta
Output in KW	9.3
Voltage in volts	415 ±10%
F.L.Current in Amps	17
Speed in RPM	2920
% Efficiency	88.9(IE2)
Protection	IP-55
Power Factor	0.83
BRG DE	6309 ZZC3
BRG NDE	6309 ZZC3

ALL DIMENSIONS ARE IN mm					PREPARED	H.H	02-12-2023	LAKSHMI ELECTRICAL DRIVES LIMITED COIMBATORE - 641 004	
LINEAR DIMENSIONS (MACHINING)	GENERAL TOLERANCES					CHECKED	V.B		02-12-2023
	ABOVE	0	30	100	300	APPROVED	R.R		02-12-2023
	UPTO	30	100	300	1000	SCALE	NTS		
	TOL	±0.2	±0.3	±0.5	±0.8	QUANTITY	1 No		
ANGLES	± 1/2'					MATERIAL			
DCR. NO	ZONE	ALTERATIONS			SIGN/ DATE	WEIGHT IN kg.	ROUGH FINISHED	RAW MATERIAL CODE	
		MODEL	LE 160 M	DRG.No.	LE16023001	REV. NO	00		