



LAKSHMI ELECTRICAL DRIVES PRIVATE LIMITED.,

Coimbatore - 641 004.

TECHNICAL DATA SHEET - 0.12 kW 4 POLE INDUCTION MOTOR

1	Customer:	
2	Product no:	LEH06343001
3	Output power (kW)	0.12
4	Output power (HP)	0.16
5	Phase	3
6	Polarity	4
7	Frame	63
8	Voltage (V)	415±10%
9	Frequency & it's variation (Hz)	50±5%
10	Connection	STAR
11	Insulation class	F
12	Ambient temp (Deg. C)	50
13	Duty	S1
14	Mounting	B3
15	Applicable code	IS12615/IEC 60034-1
16	Type reference	Sq. Cage Induction motor
17	Full Load Current (Amps)	0.62
18	Full Load Torque -(Nm)	0.86
19	Full Load Speed (rpm)	1340
20	Starting Current as % of FLC	600
21	Starting Torque as % of FLT	160
22	Break down or Pull-out Torque % FLT	220
23	%Efficiency at 100%	64.8(IE3)
24	at 75%	63.8
25	at 50%	58
26	Power factor at 100%	0.6
27	at 75%	0.56
28	at 50%	0.51
29	Temperature Rise	B CLASS LIMIT
31	Moment of Inertia	0.00168
32	Direction of Rotation	Bidirectional
33	Coupling/Pulley	Direct/Flexible
34	Method of Cooling	IC411
35	Enclosure	TEFC
36	Protection	IP55
37	Bearing type	Deep Groove Ball Bearing
38	Bearing no. DE/NDE	6202 2RS C3 / 6202 2RS C3
39	Paint/Coating	RAL 7046
40	Material of Construction	Aluminium
41	Shaft Material	EN8
42	Relative Humidity	<90
43	Terminal box position	TOP
44	No of terminals	3
45	Working Altitude level.	1000 MT
46	Additional Requirement	As per customer request

Efficiency Values are without seals.

Performance Data subject to tolerance as per IS: 12615:2018