


EXTENSION DETAILS



TERMINAL BOX DETAILS

NAME PLATE DETAILS (S12815:2018)

Marking	CE
Frame	LE 80
Duty	S1
Class of Insulation	F
Frequency, Hz	50±5%
Pole	4
Connection	STAR
Output in kW	0.75
Voltage in Volts	415±10%
F.L.Current in Amps	2.2
Speed in RPM	1410
% Efficiency	92.5(IE3)
Brg.(OE)	6204 2RSC3
Brg.(NDE)	6204 2RSC3
Power Factor	0.74
Protection	IP55

ALL DIMENSIONS ARE IN mm

GENERAL TOLERANCES

LINEAR DIMENSIONS (MACHINING)	ABOVE 0	30	100	300
UP TO	30	100	300	1000
TOL	±0.2	±0.3	±0.5	±0.8

ANGLES ± 1/2°

PREPARED K.SP 11-06-2024

CHECKED ASP 11-06-2024

APPROVED K.K.N 11-06-2024

SCALE NTS

QUANTITY 1 No

MATERIAL

WGT IN KG. ROUGH FINISHED

LAKSHMI ELECTRICAL DRIVES PRIVATE LIMITED
COMBATORRE - 641 004

G.A DRAWING
0.75KW, 4 POLE, IE3

MODEL LE 80 DRG.No. LEH08043002 REV. 00

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27