


TERMINAL BOX DETAILS



EXTENSION DETAILS

NAME PLATE DETAILS (IS 12615 : 2018)	CE
MARKING	CE
Frame	LE 160 M
Duty	S1
Class of insulation	F
Frequency, Hz	50 ±5%
Pole	2
Connectoin	Delta
Output in KW	9.3
Voltage in volts	415 ±10%
F.L. Current in Amps	17
Speed in RPM	2930
% Efficiency	90.7(IE3)
Protection	IP-55
Power Factor	0.9
BRG DE	6309 ZZC3
BRG NDE	6309 ZZC3

ALL DIMENSIONS ARE IN mm

GENERAL TOLERANCES

LINEAR DIMENSIONS (MACHINING)	ABOVE	0	30	100	300	1000
	UPTO	30	100	300	1000	
	TOL	±0.2	±0.3	±0.5	±0.8	

ANGLES	± 1/2°
--------	--------

PREPARED	K.SP	18-06-2024
CHECKED	ASP	18-06-2024
APPROVED	K.K.N	18-06-2024
SCALE	NTS	
QUANTITY	1 No	
MATERIAL		
WEIGHT IN Kg.		
SIGN/ DATE		

LAKSHMI ELECTRICAL DRIVES LIMITED
COIMBATORE - 641 004



GA DRAWING
9.3KW, 2 POLE, IE3

MODEL	LE 160M	DRG.No.	LEH16023001	REV.	00
-------	---------	---------	-------------	------	----